



## STANDARD FEATURES

- Similar side profile with Classic & Classic II line
- LED lighting top canopy & top shelf
- LED lighting on lower canopy & intermediate shelf
- Tilt back front glass
- Hermetic air cooled condensing unit
- Forced air refrigeration
- Refrigerated deck
- Front, top and side double glasses
- Adjustable legs
- Dixell control with diagnostic
- Cases ship standard unfinished front and stainless steel skin sides

## OPTIONS

- Non-refrigerated top
- Self-rolling night curtain
- Condensate water tray with automatic evaporating system
- S/s steps for display area
- Hot glass shelves with electric control
- Remote condensing unit
- RAL color/laminate front and sides
- Casters

CLASSIC & CLASSIC II COMBI			
TECHNICAL FEATURES		MODELS	
		CCOMBI1150	CCOMBI1650
External Dimensions (L-D-H)	Inches	45 1/4" - 37 1/8" - 47 3/4"	65" - 37 1/8" - 47 3/4"
	MM	1150 - 943 - 1213	1650 - 943 - 1213
Crated Dimensions (L-D-H)	Inches	54" - 46" - 63 1/4"	71" - 46" - 63 1/4"
	MM	1371 - 1092 - 1346	1803 - 1092 - 1346
Top Refrigeration Display Area	Type	Fan Ventilated	Fan Ventilated
Refrigeration Display Area	Type	Deck / Lower Shelf	Deck / Lower Shelf
Open Area & Top Deck			
Operating Temperature	°C / °F	+4°C / 39.2°F	+4°C / 39.2°F
Compressor	Nr./Type	1 / Hermetic	1 / Hermetic
Cooling Power @+10°C/+14°F	(W/BTU'S)	1350W / 4350BTU'S	1680W / 5320BTU'S
Electric Supply	(V/Ph/Hz)	230/1/50 (UE) 220/1/60 (USA)	230/1/50 (UE) 220/1/60 (USA)
Power Consumption	(A)	9A	13A
Defrost	Mode/Type	Electric	Electric
Climatic Class	N°/°C/°F/H.R.	4+/35/95/70%	4+/35/95/70%
Refrigerant Gas	Type	R404A	R404A
Net Weights	Kg/Lb	266Kgs / 586Lbs	350Kgs / 771Lbs
Crated Weights	Kg/Lb	391Kgs / 862Lbs	525Kgs / 1157Lbs

\* Dimensions are without side panels

\* Manufacturer reserves the right to change specifications without notice. Not responsible for error and omissions.



361-367 Beach Road, Burlingame, CA 94010  
 Tel: 855.885.2400 | 650.342.2400 | Fax: 650.342.7400  
 sales@oscartek.com | www.oscartek.com

